Program of Requirements



Project Napoleon

Owner	: Netherlands Forensic Institute
Project Name	: Napoleon
Project Number	: 310.158
Version	: 1.1
Status	: Concept
Date	: 23-09-2008



Version Status Date : 1.1 : Concept : 23-09-2008

: NFI : Napoleon : 310.158

TABLE OF CONTENTS

1	DO	CUMENT INFO	. 3
2	INT	RODUCTION	. 6
3	NA	POLEON	. 8
	3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9	PURPOSE OF THE NAPOLEON PRODUCT FUNCTIONAL REQUIREMENTS	8 9 10 10 11 11 11
4	BO	NAPARTE	13
	4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9	PURPOSE OF THE BONAPARTE PRODUCT FUNCTIONAL REQUIREMENTS CONSTRAINTS OPERATIONAL REQUIREMENTS RELIABILITY REQUIREMENTS MAINTENANCE REQUIREMENTS SYSTEM REQUIREMENTS SECURITY REQUIREMENTS USABILITY	13 13 18 19 19 19 19
	4.10	Phase 2	19



Version Status Date : 1.1 : Concept : 23-09-2008

: NFI : Napoleon : 310.158

1 Document Info

Document History

Version	Date	Status	Author	Change description
0.1	29-05-2008	Concept	10, 2, e	Draft; after discussions with SNN on 22-05-2008 and 10, 2, e on 26-05-2008. Describes requirements for phase 1, with basic functionality.
0.2	05-06-2008	Concept		After discussion with 10, 2, e
0.3	07-06-2008	Concept		After discussion with SNN on 05-06-2008. Revised by 10, 2, e
0.4	13-06-2008	Concept		Comments SNN processed.
0.5	23-06-2008	Concept		Comments of 10 2 e (ICMP) processed.
0.6	02-07-2008	Concept		Comments of 10, 2, e processed.
1.0	14-07-2008	Preliminary		Comments SNN processed. This version is the baseline for phase 1; phase 2 will be elaborated in future versions.
1.1	18-09-2008	Concept		Update after discussions with SNN and the creation of the Functional Designs for Bonaparte and Napoleon. Chapter 5 (on Workflow, informative only) has been removed
2.0	t.b.d.	Approved		Approved by ONN and NFI.

Table of References

Reference [ref]	Title	Author	Version	Comments
Bonaparte	Bonaparte: Bayesian networks for victim identification on the basis of DNA profiles	SNN	2.1	
Napoleon	Research Proposal Napoleon (PID)	NFI	2.0	



: NFI : Napoleon : 310.158 : 1.1

Version Status Date : 1.1 : Concept : 23-09-2008

Acronyms en definitions

Acronym	Description
(CODIS) Case ID	CODIS-key: NFI-case ID + KLPD#
Allele	Number of repeating DNA-blocks on a Locus
Batch	Search definition within all DNA profiles in a database, based on a selection of
	characteristics. Batches are not bound to Projects or Folders
BSO	Biologisch Sporen Onderzoek
CODIS	Combined DNA Index System, application that is licensed by S.A.I.C, USA, under
man and the second states	permission of the FBI. Installed version at NFI: 5.7.3.
CODIS DVP	NFI Database containing DNA profiles of missing persons ("Databank Vermiste
	Personen"), family members of missing persons and of unidentified bodies based on
	CODIS
CODIS Specimen	MP: Missing Person [relation code: A, B]
Category	UP: Unidentified Person [O, P, Q, R]
	EK: Elimination known [n.a.]
	MP-relative:
	 B(iological)F(ather) [F], BM(other) [M], BC(hild) [C, D, E], BS(ibling) [S, T, U,X]
	 P(aternal) R(elative) [n.a], MR [n.a.]
	EK: Elimination known [n.a.]
	n.a.: Spouse [2] Deta halenning to a Chaptering (such as #Lasi, profile, alleles ata.)
CODIS Specimen	Data belonging to a Specimen (such as #Loci, profile, alleles etc.)
CODIS Specimen	Unique ID for a DNA profile (Detabase apositie, e.g. in CODIS:
	SIN# + Rol + Appyragenummer
DMZ	Demilitarized Zone, physical or logical sub network that contains and exposes an
	organization's external services to a larger untrusted network usually the Internet
DNA profile	See Profile
DT&B	Digitale Technologie en Biometrie
FM	Family Member (Father Mother Child)
Folder	Collection of Projects with a common characteristic such as "Srebrenica". "Suriname"
	resp. "DVP" and common match criteria.
GUI	Graphical User Interface
ICIS	Interactive Collaborative Information Systems (http://www.senternovem.nl/bsik/projecten
	/ict/icis_interactive_collaborative_information_systems.asp)
ICMP	International Commission on Missing Persons (http://www.ic-mp.org)
Individual	Individual person (can be either a UI or a person in a Pedigree)
	An Individual belongs to exactly one Project.
Locus	Position of a STR on a chromosome
Mixed profile	DNA profile of a contaminated specimen, containing DNA material of multiple individuals
MP	Missing Person. A MP can have a Profile.
Mutation model	Probability distribution of mutations between allele-pairs of a Locus.
(uniform)	Uniform Mutation model (default) assumes that there is a propagation probability P for
	each allele. The remaining probability (1-P) is distributed evenly over mutation towards
	one of the other alleles. See Dawid et. Al.
NFI	Netherlands Forensic Institute
NFI#	NFI case number
Null-allele	Also called "silent" allele: a DNA replication artifact due to allele dropout causing the
DE	allele to be invisible as a peak in the DNA profile.
PE	Personal Effect (a.k.a. Personal item), object believed to belong to a Missing Person,
Dediana	such as a toothorush containing DNA material.
Pedigree	Construction of the mutual relations between missing persons and their relatives.
Profile	Anonymous DNA profile related to a case.

: NFI : Napoleon : 310.158

Version Status Date : 1.1 : Concept : 23-09-2008

Acronym	Description
(AM, PM)	A UI profile is Post Mortem (PM), collected from unidentified remains.
	An Ante Mortem (AM) profile is either:
ing and see	collected from a family member of a missing person
	collected from a personal item, such as a toothbrush of a missing person
Project	Work set within Napoleon, consisting of one or more DNA profiles e.g. linked to the same missing person, Pedigrees or unidentified person.
oniteo onite	• 0 or more unidentified individuals
	O or more (nutative) AM profiles (A putative AM profile can be a PM profile)
	 O or more (putative) Pedigrees
	If a Pedigree consists of more missing persons, it could be stored in one Project.
Role	Role in a Pedigree, relative to the MP: (Father, Mother, Child, Sibling, PE, unidentified)
Search Count	Number of times a profile was searched for
Search Set	Set of UIs to be matched. A Search Set is part of a Project.
SIN	Specimen Identification Number, represents a "Stuk van Overtuiging"
SNN	Stichting Neurale Netwerken
SNP	Single Nucleotide Polymorphism
Specimen Type	Also known as Specimen Category.
	Attribute designating the type of a DNA profile, such as "MP", "BM", "BF", etc.
STR	Short Tandem Repeat, repetitions of tiny pieces of DNA, used for matching because they can vary strongly between individuals
UI	Unidentified Individual or Personal Effect ¹
Virtual profile	Constructed profile, combining two or more partial DNA profiles
XML	Extended Markup Language

¹ A PE is either positively belonging to an Individual (e.g. a tooth from youth) or maybe belonging to an Individual (e.g. a toothbrush, which might also belong to a sibling). In the first case the PE acts as a FM, in the latter it acts as a UI.



: NFI : Napoleon : 310.158

Version Status Date : 1.1 : Concept : 23-09-2008

2 Introduction

Napoleon is a system for identification of unidentified victims through screening and matching of their DNA profiles against Pedigrees of Missing Persons' DNA Profiles in large databases based on a Bayesian statistical network analysis approach.

The development of Napoleon will be performed and supported by the following parties:

Netherlands Forensic Institute (NFI)

- Department Biologisch Sporen Onderzoek (BSO)
- Department Digital Technology and Biometrics (DTB)

Stichting Neurale Netwerken (SNN)

the Dutch Foundation for Neural Networks, a national network of research groups on neural networks, machine intelligence and affiliated techniques. SNN Nijmegen, the research group 10.2.g will be involved in this project.

International Commission on Missing Persons (ICMP)

 Research lab in Bosnia which is responsible for identifications of victims in former Yugoslavian countries, after Tsunami disaster, Katrina hurricane and after other disasters.

Within the Napoleon research project the aim is to develop new software in which the whole Pedigrees of the relatives of missing persons are used in both the screening and the matching phase. The main advantage of this approach is that the number of false hits will be much lower than conventional methods. The software will consist of database functions, a graphical user interface and screening and matching functionality. The Matching of Missing Persons against its Pedigree's in large databases will be based on a Bayesian statistical network analysis approach. In this way the Napoleon system will improve the quality and continuity of the services delivered by the NFI, even in case of a major disaster. The combination of both the Pedigree Approach and the Bayesian Approach is new in DNA identification work.

Within the Napoleon project two complementary products will be developed:

- Napoleon-product: the Logistics modules to be developed by NFI
- Bonaparte product: the Calculation core to be developed by SNN

These products will be specified in the following chapters. As a rough indication, the domains of both products are sketched globally in the picture below.



Version Status Date

: 1.1 : Concept : 23-09-2008

: Napoleon

: NFI



Figure 1: the Napoleon and Bonaparte domains

The project is divided into two phases :

- Phase 1: Autosomal DNA profiles •
- Phase 2 : Extended profiles •

The distinction between these two phases is indicated in the text, where relevant. Phase 1 focuses on good-quality profiles and the general feasibility and usability of the method, whereas phase 2 is concerned with refining and extending the method.



Version Status Date : 1.1 : Concept : 23-09-2008

: Napoleon

: 310.158

: NFI

3 Napoleon

3.1 Purpose of the Napoleon product

The Napoleon software takes care of the logistic handling of data and results:

- Preparing the input data for Bonaparte
- Maintaining the Napoleon database concerning groups, users, security, reporttemplates and logging.
- Reporting the Bonaparte match results

3.2 Functional requirements

3.2.1 Data Preparation

[NF001] Import data

Napoleon shall be able to read the export files of several native and foreign databases. (phase1: CODIS DVP, ICMP and some proprietary formats used for validation purposes). This is a one-way interface. No information shall be fed back into the data sources.

Independent on the source database Napoleon shall translate the export file into a XML-file with a standard syntax (still to be defined).

Napoleon associates all imported profiles with at least:

- Role
- Project
- Folder

This associated information will be used by Bonaparte to configure matches.

Role	Туре	DNA present	ID known	Description
FM	Reference	\checkmark	1	Family Member (1 st degree: F, M, C, S)
UI	Target	\checkmark	x	Unidentified Individual
PE	Target	~	possibly	Personal Effect, either UI (no ID) or FM (ID)
MP	Target	x	\checkmark	Missing Person

Possible Roles (using CODIS as example):

3.2.2 Maintenance

[NF002] Format flexibility

Identification fields used in database structures, such as Specimen ID numbers, must be flexible so that data from various sources can be processed.



Version Status Date : 1.1 : Concept : 23-09-2008

: Napoleon : 310.158

: NFI

Minimal sources are CODIS DVP, the ICMP database and Test databases.

[NF004] DNA-profile manipulation Obsolete, contained in [BF003]

[NF005] Static Data Configuration Obsolete, contained in [BF002]

[NF006] Archiving (phase 2) Obsolete, joined with [BF009]

3.2.3 Reporting

[NF007] Reporting features

Napoleon can deliver the following user specified Reports using data from the Napoleon internal database:

- 1. Match Reports (NFI)
- 2. Match Reports (ICMP)
- 3. Match Reports (ad-hoc) (phase 2)
- 4. Deleted-Reports, when a case is (virtually) deleted from Napoleon

[NF008] Report archeology (phase 2)

It may occur that a case has to be re-examined. When that case was already archived (deleted from the current workspace) it should be possible to reconstruct the context of the case report, so that the findings can still be confirmed.

3.3 Constraints

[NC001]

The technical environment in which Napoleon is developed should be MySQL/Java and Flexible or Open source platforms, as far as performance requirements permit this.

[NC004]

The XML-conversion of databases to be imported should be compatible to the DNA profile structures used by CODIS DVP and the ICMP (phase 1) as well as Excel Validation data in ad-hoc formats. In a later stage other conventions may be added.

[NC006]

Napoleon must be validated with a proper test-set to be defined by NFI and ICMP. Note: DNAview cannot be used as a formal (commercial) validation reference (prohibited by Brenner). Probably Familias will be used for this purpose.

[NC007]

	Owner Project Name Project Number	: NFI : Napoleon : 310.158
æ	Version Status Date	: 1.1 : Concept : 23-09-2008

The interfaces with databases containing DNA profiles, or exports from databases, are read-only and limited to DNA profiles with their reference information, such as case-id etc. Napoleon does not feed back any information into its source databases.

[NC008]

There is no direct interface between Napoleon and its source databases.

[NC009]

Linkage (relations between alleles) is not applied within Napoleon, except possibly for phase 2 when SNP is included.

3.4 Operational requirements

[NO001] Client-server and standalone mode Napoleon will be able to run standalone (phase 2) on a commodity laptop as well as in a network environment with multiple users (phase 1) in a client-server architecture.

The maximum number of concurrent users is 20 Forensic Researchers and/or 50 Dataenterers (might be needed in the event of a calamity)

[NO002] Logging of actions

All searches and decisions made by the user shall be logged, specifying time, user and action.

[NO003] User administration

A user-administration must be set up. This administration contains the known users and their according rights to operate Napoleon and provides Role Based Access Control.

The following User Roles and according privileges are identified:

User Role	Privileges	Comments		
Administrator all		System administrator. Includes the		
	그 위의 한 것을 못한 것 같아. 한 시간	SNN maintenance user)		
Data Enterer	Basic maintenance	Data Entry (profiles, Pedigrees, etc.)		
Forensic Researcher	Matching,	NFI personnel or ICMP-personnel		
a store distribution in	Basic maintenance			

3.5 Reliability requirements

[NR001] Backups

There shall be periodic automatic backups so that little work will be lost in case of problems. After recovery at most one hour of work can be lost. The backup only concerns the internal Napoleon database.

An automatic permanent backup is made daily.



Version Status Date : 1.1 : Concept : 23-09-2008

: Napoleon

: 310.158

: NFI

3.6 Maintenance requirements

[NM001] Compatibility

Napoleon's interface conversion modules must keep up with:

- new releases of source databases
- new statistical models
- new DNA kits (LociSets)

[NM002] Export

For each selected database source, Napoleon shall supply export functionality, as far as not contained in the source database itself.

[NM003] Use of 3rd party products

All 3rd party products applied in Napoleon should be acquired from reliable suppliers, offering transparent conditions for usage, upgrade and maintenance.

[NM004] Documentation

Clear design documentation and manuals are needed for the use and maintenance of Napoleon.

3.7 System requirements

[NS001] Interfacing with databases

Napoleon will have database interface modules allowing it to read exports from CODIS DVP, ICMP and other foreign DNA-databases.

3.8 Security requirements

[NX001] Authorization

Only authorized users may gain access to Napoleon through a login procedure. Napoleon starts up with an authorization-dialog.

After a configurable period of inactivity the authorization dialog reappears, so that the user has to log in again.

[NX002] Privacy

From NFI's viewpoint it is preferred that no privacy sensitive information is contained within Napoleon.

Napoleon should nevertheless *be capable* of containing privacy sensitive information. This information might be very useful in checking the consistency of matches, and other potential users may require the use of such data.

Specifically the following text fields must be accommodated:

Name



Version Status Date : 1.1 : Concept : 23-09-2008

: Napoleon

: 310.158

: NFI

- Date of Birth
- Gender
- Ethnical group (population)
- Residence
- Finding place of sample
- "Missing since" date

plus some future-use fields.

The use of each field must be configurable. If a field is not configured for use, it is invisible to the user and contains no data (default setting for NFI-use).

If privacy sensitive information is used and stored, it must be encrypted such that it can only be reconstructed by using Napoleon (phase 2).

[NX003] Secure connections

No insecure open internet connections may be applied.

3.9 Usability

[NU001] Look and Feel

The GUI is designed to be intuitive, conforming to universal GUI-guidelines.

[NU002] User Profiles

Napoleon shall support user-profiles containing preferred settings, etc.



Version Status Date : 1.1 : Concept : 23-09-2008

: Napoleon : 310.158

: NFI

4 Bonaparte

4.1 Purpose of the Bonaparte product

The project "Bonaparte" will deliver a system for kinship analysis in DNA-files as described in the ICIS valorization proposal [Bonaparte].

This system, the computational core of Napoleon, will be referred to as "Bonaparte".

Bonaparte consists of 3 elements:

- Computational core
- Preparing the Match
- Communication Protocol

4.2 Functional requirements

4.2.1 Computational Core

The computational core performs the screening and matching. Matching can be done either automatically or manually.

Automatic Matches consist of ("UI vs. anything"):

- direct match UI vs. UI
- direct match UI vs. PE
- kinship match UI vs. MP (Pedigree)

Manual matches can consist of ("anything vs. anything"):

- direct match UI vs. UI
- direct match UI vs. PE
- kinship match UI vs. MP (Pedigree)
- kinship match PE vs. MP (Pedigree)
- kinship match MP vs. MP (not likely)

Note that matching a MP is in fact matching against the MP's Pedigree (there is no DNA-profile of the MP self).

Note also that there is no direct matching against references (only kinship matching)

The computational core shall support the following features:

[BF001] Elementary matching

Elementary matching options (Search Set vs. Batch), where x, y are numbers [1,N]

Direct matches:

- 1. x UI vs. y UI (to detect doubles)
- 2. x UI vs. y PE

	Owner Project Name Project Number	: NFI : Napoleon : 310.158
<u>A</u>	Version Status	: 1.1 : Concept

Kinship matches:

- 3. x UI vs. y Pedigrees; match UI-profiles into (putative) Pedigrees
- 4. x UI vs. y FM (1:1) to detect parents, children and siblings in Pedigrees, with the same role as in the current Pedigree: this means that for the screening to detect parents and children only the family members with the roles F, M and C are involved. To detect siblings only the family members with the role S are involved.
- 5. (phase 2) x UI vs. y UI (to detect parents, children and siblings)

[BF002] Network builder

Build Bayesian network family – per locus

- 1. Paternal/Maternal inheritance
 - a. Mutation model (such as from Ayres or Brenner.
 - In phase 1 only the uniform mutation model will be applied)
- 2. Genotype observation
 - a. Alleles, KIT
 - b. Multiple genotypes with their according probabilities²
- 3. Population allele frequencies
- 4. Theta-correction
- 5. Rare alleles
- 6. Null-alleles
- 7. Size bias correction models

It is acknowledged that applying complex models or corrections will impair the system performance. Performance benchmarking on screening will be done with simple models and corrections, whereas more complex models and corrections will only be applied for validation purposes (in phase 2).

(SNN will investigate the performance effects of the selection of corrections and models)

4.2.2 Preparing the Match

The GUI shall allow the user to

- enter configuration data and selections for the computational core
- perform basic manipulations on Profiles, Folders and Projects
- manipulate Pedigrees

[**BF003**] Profile Management³

The following operations are possible with profiles. Reference is the Napoleon internal database. Adapted profiles are never fed back into the source-database.

For profiles constructed through the Napoleon GUI:

- 1) Add a profile (NB: an artificial profile must be clearly marked as being artificial)
 - a) Family Member (FM)
 - b) Personal Effect (PE)

² Possibly to be related to peak-heights in a later stage (phase 2 or later). NB mixed profiles are excluded from the computational core in both phase 1 and 2. However the data-storage should be prepared for storing mixed profiles which may be dealt with in future versions.

³ The system will compute with at most one (maybe virtual) profile per individual.



Owner: NFIProject Name: NapoleonProject Number: 310.158

Version Status Date : 1.1 : Concept : 23-09-2008

- c) Victim (UI)
- d) Body Part (UI)
- 2) Edit/Change a profile (NB: an adapted profile must be clearly marked as being artificial)
 a) Population⁴
 - a) Population b) Podiaroo rofor
 - b) Pedigree reference(s)
 - c) Alleles
 - d) Add Loci

For external profiles:

3) Import profiles from an external source (XML or Excel)

For any profile:

- 4) Export profiles to an external file (XML-interface t.b.d.)
- 5) (phase 2) Construct a virtual profile (e.g. add up of profile parts supposedly belonging to the same victim, or making a test-profile)

[BF004] Construction of Pedigrees

The Bonaparte GUI offers a tool to construct Pedigrees graphically. Pedigrees consist of squares (males) and circles (females), where the color represents the status being either

- "no DNA sample" = checked square/circle,
- "reference sample" = blank square/circle,
- "missing person" = red square/circle,

Pedigrees may be composed by dragging Individuals from the Project onto positions in the Pedigree. Role information already present in the source data defines a "basic" Pedigree; this is presented by the Pedigree builder as first guess (a FMC-tree, Father, Mother, Child). Next to the FMC-tree, the Pedigree Editor automatically shows the according MC-tree (where the F-role is blank) and the according FC-tree (where the M-role is blank). If there is no role information in the imported data no basic Pedigrees will be drawn.

It shall be possible to define relations within the Pedigree such as: there is a 10% chance that a particular child is not of the supposed biological father.

For phase 1 there will only be input/output of Pedigrees through the Napoleon GUI. Note that a Pedigree can "evolve" by dragging Individuals onto its positions. A PM profile may act as an AM reference profile when it is dragged onto a reference-position (it will always remain a target however). See also "Appendix on Pedigrees".

One project may contain several (putative) Pedigrees. A (putative) Pedigree can be excluded from use in Matching.

[BF005] Pedigree Consistency Check

During composition the consistency of a Pedigree is assessed. Any change in the Pedigree (such as by editing it) will be checked in the background. The system will return a consistency measure after each update of the Pedigree, and present the number of mismatches contained in it.

⁴ For phase 1 Population is coupled to a Match, not to an individual profile, In later stages the default Population-value of a Match might be overruled by a profile-bound Population-value. For phase 1 however, this field is unused.

-		Owner Project Name Project Number	: NFI : Napoleon : 310.158
1	States and States and States and	Version	: 1.1
and the second		Status Date	: Concept : 23-09-2008

Judgment of the overall consistency is left to the user, who may decide to accept, reject and/or store the Pedigree, or adapt the Pedigree until the Pedigree is considered sufficiently consistent.

[BF006] Match Preparation

The Bonaparte GUI will list the automatically imported data/new projects and earlier defined projects. Data affected by automatic searches will be distinguished from unaffected data.

A (set of) NFI-case(s) may be given a name so that the project can be easily found again. New imported data: user should define a project name and may add Pedigree(s).

For the match preparation the user should define the Search Set Now the list with Individuals belonging to the selected project is presented in a list, together with the attribute "Specimen category", for the Search Set.

Next a Batch can be defined within a Folder.

The following criteria can be used to create a batch:

- Folder Name
- Project name
- Specimen Type

The created batch is the matching set for the Search Set; it cannot be saved as a separate entity within a Folder, but its use in a Match is logged.

There can be selectable predefined Batches.

The user may now select the option "match", to start the Match-Setup dialog.

[BF007] Match Parameters

Match Parameters can be applied on two levels: Folder and Project. For automatic searches the Folder-level Match Parameters are applied For manual searches the Project-level Match Parameters supersede the (default) Folderlevel Match Parameters. The following Match Parameters must be set:

Direct Matches:

- 1) LR-threshold
- 2) Population Type
- 3) Subpopulation correction (Θ -correction)
- 4) Size bias correction model (or specify a customized size bias correction model)
- 5) Prior odds
- Kinship Matches (extra parameters compared to direct matches):
- 6) Mutation model (or specify a customized mutation model)
- 7) Model for null alleles
- 8) Model for rare alleles
- 9) Error model



Owner: NFIProject Name: NapoleonProject Number: 310.158

Version Status Date : 1.1 : Concept : 23-09-2008

On Folder-level, where the default Match Parameters are specified, it also has to be specified against which other Folders and Elimination Projects (see BF011] the Folder has to be automatically matched.

The same remark with respect to performance as in [BF001] applies.

[BF008] Match and Presentation of results

The results of the match are presented to the user.

Minimal content of the Hitlist (layout is to be determined):

- 1) Date, Issuer, Project, Search Set, Batch, Match strategy summary, Case ID
- 2) List of Hits 1 { UI/MP | Reference | LR | #Loci } N

The Hitlist may be filtered as follows:

- Thresholds, such as LR, min. # loci, max. # mutations
- Statistics type
 - LR (likelihood Ratio)
 - Posterior odds

Detailed information will be shown on selection of a Hit:

- Date, Issuer, Project, Search Set, Batch, Match strategy summary, Case ID, Folder
- Pedigree
- LR per Locus
- DNA profiles

The detail report can be exported and printed. The DNA profiles of the Set can be exported for comparison purposes.

Matches must be confirmed by the user. When a UI is confirmed to match with a MP, then the UI is referred to as the Profile of the MP, while the UI refers to the MP for the Identity. They are <u>not</u> merged within Napoleon, but continue as separate Individuals. The merging of Individuals as a result of a match is done outside the scope of Napoleon.

[BF009] Creating Folders and Projects

Projects are formed around one or more MPs (if those MPs are present in the same Pedigree) and/or one or more UIs. Projects can be grouped in Folders. Both Folders and Projects can be created new.

After some time a Folder or Project(s) may become obsolete so that the user does not want to see these Folders/Projects in selection lists anymore.

Such Folders/Projects can be archived. This means that they are removed from the current workspace, but can still be recovered and put back in the current workspace. This feature can be used in case of audits or re-opening old cases.

[BF010] Refresh Folders and Projects

Periodically (configurable) the contents of the export of source database may have changed, e.g. profiles were added. These changes may affect Projects and/or Folders.

	Owner Project Name Project Number	: NFI : Napoleon : 310.158
æ	Version Status Date	: 1.1 : Concept : 23-09-2008

Napoleon should warn the user for this and present the list with possibly affected Projects/Folders.

All new data should be either:

- Added to an existing Project
- Put into a new Project

The user may now decide to (automatically) update the affected Projects/Folders with a new Search.

[BF011] Elimination of Profiles

Profiles can belong to persons that may have contaminated samples in the process, such as policemen, lab-personnel, etc.

Such Profiles are clustered in Elimination Projects, which are on their turn contained in the so-called Elimination Folder.

The automatic search feature eliminates Hits with Profiles from Elimination Projects that are coupled to Folders (see BF007]).

4.2.3 Communication Protocol

Exchange of data between Napoleon and Bonaparte is implemented through the common internal Napoleon database (see Figure 1) or by XML-format files.

The exact content of the data (and the data model) are still to be elaborated.

Napoleon is responsible for preparing the right input data in the internal database, and place it in a workspace. Bonaparte can import this prepared data and export results to the workspace.

4.3 Constraints

Napoleon's constraints (paragraph 3.3) NC001, NC002, NC006 and NC009 apply to Bonaparte as well.

[BC001]

Mixed profiles are excluded from the computational core. However the data-storage should be prepared for storing mixed profiles.

[BC002]

The Bonaparte database stores percentages (one genotype with 100% percentage). Peakheights will not be stored.

4.4 Operational requirements

Napoleon's operational requirements NO001 ad NO002 apply to Bonaparte as well.

	Owner Project Name Project Number	: NFI : Napoleon : 310.158
n n	Version	: 1.1
	Status	: Concept
	Date	: 23-09-2008

[BO001] Performance

The time needed to perform 100 UI vs. 100 basic Pedigrees (F + M + C = MP) matches shall not exceed 1 minute, applying a uniform mutation model.

[BO002] Operational Quality

The operational quality of Bonaparte shall be verifiably better than with the currently used method, in particular in the case of many UI's and MP's with kinship information. Verification, validation and quantification (false hits, true hits, operational processing times) still has to be worked out (a.o. dependent on external factors such as data quality).

4.5 Reliability requirements

[BR001] Search count

The number of searches performed on a specimen shall be written in the specimen data (like the search count in CODIS DVP).

4.6 Maintenance requirements

Napoleon's maintenance requirements (paragraph 3.6) NM001, NM003 and NM004 apply to Bonaparte as well.

4.7 System Requirements

4.8 Security requirements

Napoleon's security requirement (paragraph 3.8) NX003 applies to Bonaparte as well. In particular, Bonaparte will not be provided privacy sensitive information.

4.9 Usability

Napoleon's usability requirements (paragraph 3.9) apply to Bonaparte as well.

[BU001]

Bonaparte shall support the use of user-profiles, such that Napoleon user-preferences connected to a user-profile (see requirement NU001) are automatically applied.

[BU002]

The parameters used in the model shall be transparent to the user and adaptable where relevant.

[BU003]

A user training shall be part of the delivery.

4.10 Phase 2

This paragraph describes extra requirements for the second phase of the project.

2		
a		
H		

Owner: NFIProject Name: NapoleonProject Number: 310.158

Version Status Date : 1.1 : Concept : 23-09-2008

These requirements will be detailed in future versions of this document, together with the referenced phase 2 features in the remaining text of this document.

In general:

- 1. Working with:
 - 1.1. Y-chromosome profiles
 - 1.2. SNP profiles
 - 1.3. mtDNA profiles
- 2. Construction of consensus profiles: combining test results / test profiles of more than one sample to one profile.
- Construction of virtual profiles: combining partial results / test profiles of one sample to one profile.
- 4. Exclusion of paternal or maternal relation in a match

For the Calculation core:

- 5. Expand the Bayesian network with:
 - 5.1. linkage between SNP-markers
 - 5.2. Y-chromosomal data
 - 5.3. mtDNA data
 - 5.4. mutation model of Xu et al, 2000
 - 5.5. genotype observation model with kit-specific parameters (possibly STR peak heights)
 - 5.6. combining observations for a sample (virtual profiles)
- 6. Expand the Matching with:
 - 6.1. virtual profile calculation
 - 6.2. clustering of profiles into consensus profile
- 7. QA calculation
 - 7.1. posterior probability genotype error
 - 7.2. posterior probability mutation

: NFI : Napoleon : 310.158

Version Status Date

: 1.1 : Concept : 23-09-2008

For the Preparation of Match:

- 8. Add profile functionality for
 - 8.1. Create profile groups
 - 8.2. Convert profiles (ordered in groups/databases)
 - 8.3. Y-chromosomes
 - 8.4. SNP-data
 - 8.5. mtDNA data
 - 8.6. management of virtual profiles
 - 8.7. management of consensus profiles
- 9. Static data configuration
 - 9.1. specify DNA-kit parameters per locus and/or group of loci
 - 9.2. functionality for Y-chromosomes
 - 9.3. functionality for SNP-data
 - 9.4. functionality of mtDNA-data
- 10. Analysis: Construction of virtual profiles
- 11. Matching: Construction of consensus profiles Identify/cluster all profiles belonging to one individual



Version Status Date : 1.1 : Concept : 23-09-2008

: NFI

: Napoleon

: 310.158

Appendix on Pedigrees

This Appendix presents an example Pedigree, used for focusing the discussions.

Legend:

- Squares represent males
- Circles represent females
- Red represents a Missing Person
- White represents that there is a reference profile available
- Strikethrough represents that there is no reference profile available
- Children are positioned below and between father and mother (e.g. half-sisters are between the same mother with different fathers)

geen ref.mo

The example below concerns an putative Pedigree, which had to be adapted during the match-process, because it turned out to be contradicting with 1:1 matches found.



Initial interpretation of Pedigree (a putative Pedigree)



Eventual interpretation of Pedigree, after evaluation